

The `ltfilehook` package*

Frank Mittelbach, Phelype Oleinik, L^AT_EX Project Team

June 15, 2021

Contents

1	Introduction	2
1.1	Provided hooks	2
1.2	General hooks for file reading	2
1.3	Hooks for package and class files	3
1.4	Hooks for <code>\include</code> files	4
1.5	High-level interfaces for L ^A T _E X	5
1.6	Internal interfaces for L ^A T _E X	5
1.7	A sample package for structuring the log output	5
2	The Implementation	6
2.1	Document and package-level commands	6
2.2	expl3 helpers	7
2.3	Declaring the file-related hooks	10
2.4	Patching L ^A T _E X's <code>\InputIfFileExists</code> command	10
2.5	Declaring a file substitution	12
2.6	Selecting a file (<code>\set@curr@file</code>)	14
2.7	Replacing a file and detecting loops	17
2.7.1	The Tortoise and Hare algorithm	18
2.8	Preventing a package from loading	19
2.9	High-level interfaces for L ^A T _E X	20
2.10	Internal commands needed elsewhere	20
3	A sample package for structuring the log output	21
4	Package emulations	22
4.1	Package atveryend emulation	22
	Index	23

*This package has version v1.0k dated 2021/05/25, © L^AT_EX Project.

1 Introduction

1.1 Provided hooks

The code offers a number of hooks into which packages (or the user) can add code to support different use cases. Many hooks are offered as pairs (i.e., the second hook is reversed). Also important to know is that these pairs are properly nested with respect to other pairs of hooks.

There are hooks that are executed for all files of a certain type (if they contain code), e.g., for all “include files” or all “packages”, and there are also hooks that are specific to a single file, e.g., do something after the package `foo.sty` has been loaded.

1.2 General hooks for file reading

There are four hooks that are called for each file that is read using document-level commands such as `\input`, `\include`, `\usepackage`, etc. They are not called for files read using internal low-level methods, such as `\@input` or `\openin`.

`file/before`
`file/before/...`
`file/after/...`
`file/after`

These are:

file/before, **file/before/⟨file-name⟩** These hooks are executed in that order just before the file is loaded for reading. The code of the first hook is used with every file, while the second is executed only for the file with matching `⟨file-name⟩` allowing you to specify code that only applies to one file.

file/after/⟨file-name⟩, **file/after** These hooks are after the file with name `⟨file-name⟩` has been fully consumed. The order is swapped (the specific one comes first) so that the **before** and **after** hooks nest properly, which is important if any of them involve grouping (e.g., contain environments, for example). Furthermore both hooks are reversed hooks to support correct nesting of different packages adding code to both `/before` and `/after` hooks.

So the overall sequence of hook processing for any file read through the user interface commands of L^AT_EX is:

```
\UseHook{⟨file/before⟩}
\UseHook{⟨file/before/⟨file name⟩⟩}
  ⟨file contents⟩
\UseHook{⟨file/after/⟨file name⟩⟩}
\UseHook{⟨file/after⟩}
```

The file hooks only refer to the file by its name and extension, so the `⟨file name⟩` should be the file name as it is on the filesystem with extension (if any) and without paths. Different from `\input` and similar commands, the `.tex` extension is not assumed in hook `⟨file name⟩`, so `.tex` files must be specified with their extension to be recognized. Files within subfolders should also be addressed by their name and extension only.

Extensionless files also work, and should then be given without extension. Note however that T_EX prioritizes `.tex` files, so if two files `foo` and `foo.tex` exist in the search path, only the latter will be seen.

When a file is input, the `⟨file name⟩` is available in `\CurrentFile`, which is then used when accessing the `file/before/⟨file name⟩` and `file/after/⟨file name⟩`.

`\CurrentFile`

The name of the file about to be read (or just finished) is available to the hooks through `\CurrentFile` (there is no `expl3` name for it for now). The file is always provided with its extension, i.e., how it appears on your hard drive, but without any specified path to it. For example, `\input{sample}` and `\input{app/sample.tex}` would both have `\CurrentFile` being `sample.tex`.

`\CurrentFilePath`

The path to the current file (complement to `\CurrentFile`) is available in `\CurrentFilePath` if needed. The paths returned in `\CurrentFilePath` are only user paths, given through `\input@path` (or `expl3`'s equivalent `\l_file_search_path_seq`) or by directly typing in the path in the `\input` command or equivalent. Files located by `kpsewhich` get the path added internally by the `TEX` implementation, so at the macro level it looks as if the file were in the current folder, so the path in `\CurrentFilePath` is empty in these cases (package and class files, mostly).

`\CurrentFileUsed`
`\CurrentFilePathUsed`

In normal circumstances these are identical to `\CurrentFile` and `\CurrentFilePath`. They will differ when a file substitution has occurred for `\CurrentFile`. In that case, `\CurrentFileUsed` and `\CurrentFilePathUsed` will hold the actual file name and path loaded by `LATEX`, while `\CurrentFile` and `\CurrentFilePath` will hold the names that were *asked for*. Unless doing very specific work on the file being read, `\CurrentFile` and `\CurrentFilePath` should be enough.

1.3 Hooks for package and class files

Commands to load package and class files (e.g., `\usepackage`, `\RequirePackage`, `\LoadPackageWithOptions`, etc.) offer the hooks from section 1.2 when they are used to load a package or class file, e.g., `file/after/array.sty` would be called after the `array` package got loaded. But as packages and classes form as special group of files, there are some additional hooks available that only apply when a package or class is loaded.

`package/before`
`package/after`
`package/before/...`
`package/after/...`
`class/before`
`class/after`
`class/before/...`
`class/after/...`

These are:

`package/before`, `package/after` These hooks are called for each package being loaded.

`package/before/<name>`, `package/after/<name>` These hooks are additionally called if the package name is *<name>* (without extension).

`class/before`, `class/after` These hooks are called for each class being loaded.

`class/before/<name>`, `class/after/<name>` These hooks are additionally called if the class name is *<name>* (without extension).

All `/after` hooks are implemented as reversed hooks.

The overall sequence of execution for `\usepackage` and friends is therefore:

```
\UseHook{<package/before>}
\UseHook{<package/before/<package name>>}
\UseHook{<file/before>}
```

```

\UseHook{<file/before/<package name>.sty}&
  <package contents>
\UseHook{<file/after/<package name>.sty}&
\UseHook{<file/after>}

```

code from \AtEndOfPackage if used inside the package

```

\UseHook{<package/after/<package name>)}&
\UseHook{<package/after>}

```

and similar for class file loading, except that `package/` is replaced by `class/` and `\AtEndOfPackage` by `\AtEndOfClass`.

If a package or class is not loaded (or it was loaded before the hooks were set) none of the hooks are executed!

1.4 Hooks for `\include` files

To manage `\include` files, L^AT_EX issues a `\clearpage` before and after loading such a file. Depending on the use case one may want to execute code before or after these `\clearpages` especially for the one that is issued at the end.

Executing code before the final `\clearpage`, means that the code is processed while the last page of the included material is still under construction. Executing code after it means that all floats from inside the include file are placed (which might have added further pages) and the final page has finished.

Because of these different scenarios we offer hooks in three places.¹ None of the hooks are executed when an `\include` file is bypassed because of an `\includeonly` declaration. They are, however, all executed if L^AT_EX makes an attempt to load the `\include` file (even if it doesn't exist and all that happens is “No file `<filename>.tex`”).

```

include/before
include/before/...
include/end
include/end/...
include/after
include/after/...

```

These are:

include/before, include/before/<name> These hooks are executed (in that order) after the initial `\clearpage` and after `.aux` file is changed to use `<name>.aux`, but before the `<name>.tex` file is loaded. In other words they are executed at the very beginning of the first page of the `\include` file.

include/end/<name>, include/end These hooks are executed (in that order) after L^AT_EX has stopped reading from the `\include` file, but before it has issued a `\clearpage` to output any deferred floats.

include/after/<name>, include/after These hooks are executed (in that order) after L^AT_EX has issued the `\clearpage` but before it has switched back writing to the main `.aux` file. Thus technically we are still inside the `\include` and if the hooks generate any further typeset material including anything that writes to the `.aux` file, then it would be considered part of the included material and bypassed if it is not loaded because of some `\includeonly` statement.²

¹If you want to execute code before the first `\clearpage` there is no need to use a hook—you can write it directly in front of the `\include`.

²For that reason another `\clearpage` is executed after these hooks which normally does nothing, but starts a new page if further material got added this way.

1.5 High-level interfaces for L^AT_EX

We do not provide any additional wrappers around the hooks (like `filehook` or `scrfile` do) because we believe that for package writers the high-level commands from the hook management, e.g., `\AddToHook`, etc. are sufficient and in fact easier to work with, given that the hooks have consistent naming conventions.

1.6 Internal interfaces for L^AT_EX

<code>\declare@file@substitution</code>	<code>\declare@file@substitution</code>	<code>{\file}</code>	<code>{\replacement-file}</code>
<code>\undeclare@file@substitution</code>	<code>\undeclare@file@substitution</code>	<code>{\file}</code>	

If `\file` is requested for loading replace it with `\replacement-file`. `\CurrentFile` remains pointing to `\file` but `\CurrentFileUsed` will show the file actually loaded.

The main use case for this declaration is to provide a corrected version of a package that can't be changed (due to its license) but no longer functions because of L^AT_EX kernel changes, for example, or to provide a version that makes use of new kernel functionality while the original package remains available for use with older releases.

The `\undeclare@file@substitution` declaration undoes a substitution made earlier.

Please do not misuse this functionality and replace a file with another unless if really needed and only if the new version is implementing the same functionality as the original one!

<code>\disable@package@load</code>	<code>\disable@package@load</code>	<code>{\package}</code>	<code>{\alternate-code}</code>
<code>\reenable@package@load</code>	<code>\reenable@package@load</code>	<code>{\package}</code>	

If `\package` is requested do not load it but instead run `\alternate-code` which could issue a warning, error or any other code.

The main use case is for classes that want to restrict the set of supported packages or contain code that make the use of some packages impossible. So rather than waiting until the document breaks they can set up informative messages why certain packages are not available.

The function is only implemented for packages not for arbitrary files.

1.7 A sample package for structuring the log output

As an application we provide the package `structuredlog` that adds lines to the `.log` when a file is opened and closed for reading keeping track of nesting level es well. For example, for the current document it adds the lines

```
= (LEVEL 1 START) t1lmr.fd
= (LEVEL 1 STOP) t1lmr.fd
= (LEVEL 1 START) supp-pdf.mkii
= (LEVEL 1 STOP) supp-pdf.mkii
= (LEVEL 1 START) nameref.sty
== (LEVEL 2 START) refcount.sty
== (LEVEL 2 STOP) refcount.sty
== (LEVEL 2 START) gettitlestring.sty
```

```

== (LEVEL 2 STOP) gettitlestring.sty
= (LEVEL 1 STOP) nameref.sty
= (LEVEL 1 START) ltfilehook-doc.out
= (LEVEL 1 STOP) ltfilehook-doc.out
= (LEVEL 1 START) ltfilehook-doc.out
= (LEVEL 1 STOP) ltfilehook-doc.out
= (LEVEL 1 START) ltfilehook-doc.hd
= (LEVEL 1 STOP) ltfilehook-doc.hd
= (LEVEL 1 START) ltfilehook.dtx
== (LEVEL 2 START) ot1lmr.fd
== (LEVEL 2 STOP) ot1lmr.fd
== (LEVEL 2 START) om1lmm.fd
== (LEVEL 2 STOP) om1lmm.fd
== (LEVEL 2 START) omslmsy.fd
== (LEVEL 2 STOP) omslmsy.fd
== (LEVEL 2 START) omxlmex.fd
== (LEVEL 2 STOP) omxlmex.fd
== (LEVEL 2 START) umsa.fd
== (LEVEL 2 STOP) umsa.fd
== (LEVEL 2 START) umsb.fd
== (LEVEL 2 STOP) umsb.fd
== (LEVEL 2 START) ts1lmr.fd
== (LEVEL 2 STOP) ts1lmr.fd
== (LEVEL 2 START) t1lmss.fd
== (LEVEL 2 STOP) t1lmss.fd
= (LEVEL 1 STOP) ltfilehook.dtx

```

Thus if you inspect an issue in the `.log` it is easy to figure out in which file it occurred, simply by searching back for `LEVEL` and if it is a `STOP` then remove 1 from the level value and search further for `LEVEL` with that value which should then be the `START` level of the file you are in.

2 The Implementation

```

1 <*2kernel>
2 <@@=filehook>

```

2.1 Document and package-level commands

<pre> \CurrentFile \CurrentFilePath \CurrentFileUsed \CurrentFilePathUsed </pre>	<p>User-level macros that hold the current file name and file path. These are used internally as well because the code takes care to protect against a possible redefinition of these macros in the loaded file (it's necessary anyway to make hooks work with nested <code>\input</code>). The versions <code>\...Used</code> hold the <i>actual</i> file name and path that is loaded by L^AT_EX, whereas the other two hold the name as requested. They will differ in case there's a file substitution.</p>
--	---

```

3 </2kernel>
4 <*2kernel | latexrelease>
5 <latexrelease>\IncludeInRelease{2020/10/01}%
6 <latexrelease>          {\CurrentFile}{Hook management file}%
7 \ExplSyntaxOn

```

```

8 \tl_new:N \CurrentFile
9 \tl_new:N \CurrentFilePath
10 \tl_new:N \CurrentFileUsed
11 \tl_new:N \CurrentFilePathUsed
12 \ExplSyntaxOff
13 </2ekernel | latexrelease>
14 <latexrelease>\EndIncludeInRelease
15 <latexrelease>\IncludeInRelease{0000/00/00}%
16 <latexrelease>          {\CurrentFile}{Hook management file}%
17 <latexrelease>
18 <latexrelease>\let \CurrentFile          \@undefined
19 <latexrelease>\let \CurrentFilePath      \@undefined
20 <latexrelease>\let \CurrentFileUsed     \@undefined
21 <latexrelease>\let \CurrentFilePathUsed \@undefined
22 <latexrelease>
23 <latexrelease>\EndIncludeInRelease
24 <*2ekernel>

```

(End definition for `\CurrentFile` and others. These functions are documented on page 3.)

2.2 expl3 helpers

```

25 </2ekernel>
26 <*2ekernel | latexrelease>
27 <latexrelease>\IncludeInRelease{2020/10/01}%
28 <latexrelease>          {\_filehook_file_parse_full_name:nN}{File helpers}%
29 \ExplSyntaxOn

```

`_filehook_file_parse_full_name:nN`
`_filehook_full_name:nn`

A utility macro to trigger expl3’s file-parsing and lookup, and return a normalized representation of the file name. If the queried file doesn’t exist, no normalization takes place. The output of `_filehook_file_parse_full_name:nN` is passed on to the #2—a 3-argument macro that takes the *<path>*, *<base>*, and *<ext>* parts of the file name.

```

30 \cs_new:Npn \_filehook_file_parse_full_name:nN #1
31 {
32   \exp_args:Nf \file_parse_full_name_apply:nN
33   {
34     \exp_args:Nf \_filehook_full_name:nn
35     { \file_full_name:n {#1} } {#1}
36   }
37 }
38 \cs_new:Npn \_filehook_full_name:nn #1 #2
39 {
40   \tl_if_empty:nTF {#1}
41   { \tl_trim_spaces:n {#2} }
42   { \tl_trim_spaces:n {#1} }
43 }

```

(End definition for `_filehook_file_parse_full_name:nN` and `_filehook_full_name:nn`.)

`_filehook_if_no_extension:nTF`
`_filehook_drop_extension:N`

Some actions depend on whether the file extension was explicitly given, and sometimes the extension has to be removed. The macros below use `_filehook_file_parse_full_name:nN` to split up the file name and either check if *<ext>* (#3) is empty, or discard it.

```

44 \cs_new:Npn \_filehook_if_no_extension:nTF #1

```

```

45 {
46   \exp_args:Ne \tl_if_empty:nTF
47     { \file_parse_full_name_apply:nN {#1} \use_iii:nnn }
48 }
49 \cs_new_protected:Npn \__filehook_drop_extension:N #1
50 {
51   \tl_gset:Nx #1
52     {
53       \exp_args:NV \__filehook_file_parse_full_name:nN #1
54       \__filehook_drop_extension_aux:nnn
55     }
56 }
57 \cs_new:Npn \__filehook_drop_extension_aux:nnn #1 #2 #3
58   { \tl_if_empty:nF {#1} { #1 / } #2 }

```

(End definition for `__filehook_if_no_extension:nTF` and `__filehook_drop_extension:N`.)

`\g__filehook_input_file_seq` Yet another stack, to keep track of `\CurrentFile` and `\CurrentFilePath` with nested `\l__filehook_internal_tl` `\inputs`. At the beginning of `\InputIfFileExists`, the current value of `\CurrentFilePath` and `\CurrentFile` is pushed to `\g__filehook_input_file_seq`, and at the end, it is popped and the value reassigned. Some other places don't use `\InputIfFileExists` directly (`\include`) or need `\CurrentFile` earlier (`\@onefilewithoptions`), so these are manually used elsewhere as well.

```

59 \tl_new:N \l__filehook_internal_tl
60 \seq_if_exist:NF \g__filehook_input_file_seq
61   { \seq_new:N \g__filehook_input_file_seq }
62 \cs_new_protected:Npn \__filehook_file_push:
63   {
64     \seq_gpush:Nx \g__filehook_input_file_seq
65     {
66       { \CurrentFilePathUsed } { \CurrentFileUsed }
67       { \CurrentFilePath } { \CurrentFile }
68     }
69   }
70 \cs_new_protected:Npn \__filehook_file_pop:
71   {
72     \seq_gpop:NNTF \g__filehook_input_file_seq \l__filehook_internal_tl
73     { \exp_after:wN \__filehook_file_pop_assign:nmmm \l__filehook_internal_tl }
74     {
75       \msg_error:nnn { kernel } { should-not-happen }
76       { Tried~to~pop~from~an~empty~file~name~stack. }
77     }
78   }
79 \cs_new_protected:Npn \__filehook_file_pop_assign:nmmm #1 #2 #3 #4
80   {
81     \tl_set:Nn \CurrentFilePathUsed {#1}
82     \tl_set:Nn \CurrentFileUsed {#2}
83     \tl_set:Nn \CurrentFilePath {#3}
84     \tl_set:Nn \CurrentFile {#4}
85   }
86 \ExplSyntaxOff

```

(End definition for `\g__filehook_input_file_seq` and others.)

```

87 </2kernel | latexrelease>

```


88 <latexrelease>\EndIncludeInRelease

When rolling forward the following expl3 functions may not be defined. If we roll back the code does nothing.

```
89 <latexrelease>\IncludeInRelease{2020/10/01}%
90 <latexrelease>          {\file_parse_full_name_apply:nN}{Roll forward help}%
91 <latexrelease>
92 <latexrelease>\ExplSyntaxOn
93 <latexrelease>\cs_if_exist:NF\file_parse_full_name_apply:nN
94 <latexrelease>{
95 <latexrelease>\cs_new:Npn \file_parse_full_name_apply:nN #1
96 <latexrelease>  {
97 <latexrelease>    \exp_args:Ne \_file_parse_full_name_auxi:nN
98 <latexrelease>      { \_kernel_file_name_sanitize:n {#1} }
99 <latexrelease>  }
100 <latexrelease>\cs_new:Npn \_file_parse_full_name_auxi:nN #1
101 <latexrelease>  {
102 <latexrelease>    \_file_parse_full_name_area:nw { } #1
103 <latexrelease>    / \s__file_stop
104 <latexrelease>  }
105 <latexrelease>\cs_new:Npn \_file_parse_full_name_area:nw #1 #2 / #3 \s__file_stop
106 <latexrelease>  {
107 <latexrelease>    \tl_if_empty:nTF {#3}
108 <latexrelease>      { \_file_parse_full_name_base:nw { } #2 . \s__file_stop {#1} }
109 <latexrelease>      { \_file_parse_full_name_area:nw { #1 / #2 }
110 <latexrelease>        #3 \s__file_stop }
111 <latexrelease>  }
112 <latexrelease>\cs_new:Npn \_file_parse_full_name_base:nw #1 #2 . #3 \s__file_stop
113 <latexrelease>  {
114 <latexrelease>    \tl_if_empty:nTF {#3}
115 <latexrelease>    {
116 <latexrelease>      \tl_if_empty:nTF {#1}
117 <latexrelease>      {
118 <latexrelease>        \tl_if_empty:nTF {#2}
119 <latexrelease>        { \_file_parse_full_name_tidy:nnnN { } { } }
120 <latexrelease>        { \_file_parse_full_name_tidy:nnnN { .#2 } { } }
121 <latexrelease>      }
122 <latexrelease>      { \_file_parse_full_name_tidy:nnnN {#1} { .#2 } }
123 <latexrelease>    }
124 <latexrelease>    { \_file_parse_full_name_base:nw { #1 . #2 }
125 <latexrelease>      #3 \s__file_stop }
126 <latexrelease>  }
127 <latexrelease>\cs_new:Npn \_file_parse_full_name_tidy:nnnN #1 #2 #3 #4
128 <latexrelease>  {
129 <latexrelease>    \exp_args:Nee #4
130 <latexrelease>    {
131 <latexrelease>      \str_if_eq:nnF {#3} { / } { \use_none:n }
132 <latexrelease>      #3 \prg_do_nothing:
133 <latexrelease>    }
134 <latexrelease>    { \use_none:n #1 \prg_do_nothing: }
135 <latexrelease>    {#2}
136 <latexrelease>  }
137 <latexrelease>}
138 <latexrelease>\ExplSyntaxOff
```

```

139 <latexrelease>
140 <latexrelease>\EndIncludeInRelease
141 <*2kernel>
142 <@@=>

```

2.3 Declaring the file-related hooks

All hooks starting with `file/`, `include/`, `class/` or `package/` are generic and will be allocated if code is added to them. Thus there is no need to explicitly declare any hook in the code below.

Furthermore, those named `.../after` or `.../end` are automatically declared as reversed hooks if filled with code, so this is also automatically taken care of.

2.4 Patching L^AT_EX's `\InputIfFileExists` command

Most of what we have to do is adding `\UseHook` into several L^AT_EX 2_ε core commands, because of some circular dependencies in the kernel we do this only now and not in `ltxfiles`.

`\InputIfFileExists` loads any file if it is available so we have to add the hooks `file/before` and `file/after` in the right places. If the file doesn't exist no hooks should be executed.

```

143 </2kernel>
144 <latexrelease>\IncludeInRelease{2020/10/01}%
145 <latexrelease>      {\InputIfFileExists}{Hook management (files)}%
146 <*2kernel | latexrelease>

147 \let\InputIfFileExists\@undefined
148 \DeclareRobustCommand \InputIfFileExists[2]{%
149   \IfFileExists{#1}%
150   {%
151     \@expl@@@filehook@file@push@@
152     \@filehook@set@CurrentFile

```

We pre-expand `\@filef@und` so that in case another file is loaded in the true branch of `\InputIfFileExists`, these don't change their value meanwhile. This isn't a worry with `\CurrentFile...` because they are kept in a stack.

```

153     \expandafter\@swaptwoargs\expandafter
154     {\expandafter\@input@file@exists@with@hooks
155     \expandafter{\@filef@und}}%
156     {#2}%
157     \@expl@@@filehook@file@pop@@
158   }%
159 }
160 \def\@input@file@exists@with@hooks#1{%

```

If the file exists then `\CurrentFile` holds its name. But we can't rely on that still being true after the file has been processed. Thus for using the name in the file hooks we need to preserve the name and then restore it for the `file/after/...` hook.

The hook always refers to the file requested by the user. The hook is *always* loaded for `\CurrentFile` which usually is the same as `\CurrentFileUsed`. In the case of a file replacement, the `\CurrentFileUsed` holds the actual file loaded. In any case the file

names are normalized so that the hooks work on the real file name, rather than what the user typed in.

expl3's `\file_full_name:n` normalizes the file name (to factor out differences in the `.tex` extension), and then does a file lookup to take into account a possible path from `\l_file_search_path_seq` and `\input@path`. However only the file name and extension are returned so that file hooks can refer to the file by their name only. The path to the file is returned in `\CurrentFilePath`.

```

161 \edef\reserved@a{%
162   \@expl@@@filehook@file@pop@assign@@nnnn
163   {\CurrentFilePathUsed}%
164   {\CurrentFileUsed}%
165   {\CurrentFilePath}%
166   {\CurrentFile}}%
167 \expandafter\@swaptwoargs\expandafter{\reserved@a}%

```

Before adding to the file list we need to make all (letter) characters catcode 11, because several packages use constructions like

```

\filename@parse{<filename>}
\ifx\filename@ext\@clsextension
...
\fi

```

and that doesn't work if `\filename@ext` is `\detokenized`. Making `\@clsextension` a string doesn't help much because some packages define their own `\<prefix>@someextension` with normal catcodes. This is not entirely correct because packages loaded (somehow) with catcode 12 alphabetic tokens (say, as the result of a `\string` or `\detokenize` command, or from a T_EX string like `\jobname`) will have these character tokens incorrectly turned into letter tokens. This however is rare, so we'll go for the all-letters approach (grepping the packages in T_EX Live didn't bring up any obvious candidate for breaking with this catcode change).

```

168 {\edef\reserved@a{\unqu@tfilef@und#1\@nil}%
169  \@addtofilelist{\string@makeletter\reserved@a}%
170  \UseHook{file/before}%

```

The current file name is available in `\CurrentFile` so we use that in the specific hook.

```

171  \UseHook{file/before/\CurrentFile}%
172  \@input #1% <- trailing space comes from \@filef@und
173  }%

```

And here, `\CurrentFile` is restored (by `\@expl@@@filehook@file@pop@assign@@nnnn`) so we can use it once more.

```

174  \UseHook{file/after/\CurrentFile}%
175  \UseHook{file/after}}
176 \def\unqu@tfilef@und"#1" \@nil{#1}
177 \<latexrelease>\EndIncludeInRelease
178 \</2ekernel | latexrelease>

```

Now define `\InputIfFileExists` to input #1 if it seems to exist. Immediately prior to the input, #2 is executed. If the file #1 does not exist, execute '#3'.

```

179 \<latexrelease>\IncludeInRelease{2019/10/01}%
180 \<latexrelease>          {\InputIfFileExists}{Hook management (files)}%
181 \<latexrelease>
182 \<latexrelease>\DeclareRobustCommand \InputIfFileExists[2]{%

```

```

183 <latexrelease> \IfFileExists{#1}%
184 <latexrelease>   {%
185 <latexrelease>   \expandafter\@swaptwoargs\expandafter
186 <latexrelease>     {\@filef@und}{#2\@addtofilelist{#1}\@input}}
187 <latexrelease>\let\@input@file@exists@with@hooks\@undefined
188 <latexrelease>\let\unqu@tefilef@und\@undefined
189 <latexrelease>\EndIncludeInRelease

190 <latexrelease>\IncludeInRelease{0000/00/00}%
191 <latexrelease>     {\InputIfFileExists}{Hook management (files)}%
192 <latexrelease>\long\def \InputIfFileExists#1#2{%
193 <latexrelease> \IfFileExists{#1}%
194 <latexrelease>   {#2\@addtofilelist{#1}\@input \@filef@und}}

```

Also undo the internal command as some packages unfortunately test for their existence instead of using `\IfFormatAtLeastTF`.

```

195 <latexrelease>\expandafter\let\csname InputIfFileExists \endcsname\@undefined
196 <latexrelease>\let\@input@file@exists@with@hooks\@undefined
197 <latexrelease>\let\unqu@tefilef@und\@undefined
198 <latexrelease>\EndIncludeInRelease
199 <*2kernel>

```

(End definition for `\InputIfFileExists`, `\@input@file@exists@with@hooks`, and `\unqu@tefilef@und`. These functions are documented on page ??.)

2.5 Declaring a file substitution

```

200 <@@=filehook>
201 </2kernel>
202 <*2kernel | latexrelease>
203 <latexrelease>\IncludeInRelease{2020/10/01}%
204 <latexrelease>     {\_filehook_subst_add:nn}{Declaring file substitution}%
205 \ExplSyntaxOn

```

`_filehook_subst_add:nn` `_filehook_subst_add:nn` declares a file substitution by doing a (global) definition of the form `\def\@file-subst@<file>{\<replacement>}`. The file names are properly sanitised, and normalized with the same treatment done for the file hooks. That is, a file replacement is declared by using the file name (and extension, if any) only, and the file path should not be given. If a file name is empty it is replaced by `.tex` (the empty csname is used to check that).

```

206 \cs_new_protected:Npn \_filehook_subst_add:nn #1 #2
207   {
208     \group_begin:
209     \cs_set:cpx { } { \exp_not:o { \cs:w\cs_end: } }
210     \int_set:Nn \tex_escapechar:D { -1 }
211     \cs_gset:cpx
212       {
213         @file-subst@
214         \_filehook_subst_file_normalize:Nn \use_ii_iii:nnn {#1}
215       }
216     { \_filehook_subst_file_normalize:Nn \_filehook_file_name_compose:nnn
217       {#2} }
218     \group_end:
219   }

```

```

220 \cs_new_protected:Npn \__filehook_subst_remove:n #1
221 {
222   \group_begin:
223     \cs_set:cpx { } { \exp_not:o { \cs:w\cs_end: } }
224     \int_set:Nn \tex_escapechar:D { -1 }
225     \cs_undefine:c
226     {
227       @file-subst@
228       \__filehook_subst_file_normalize:Nn \use_ii_iii:nnn {#1}
229     }
230   \group_end:
231 }
232 \cs_new:Npn \__filehook_subst_file_normalize:Nn #1 #2
233 {
234   \exp_after:wN \__filehook_subst_empty_name_chk:NN
235   \cs:w \exp_after:wN \cs_end:
236   \cs:w \__filehook_file_parse_full_name:nN {#2} #1 \cs_end:
237 }
238 \cs_new:Npn \__filehook_subst_empty_name_chk:NN #1 #2
239 { \if_meaning:w #1 #2 .tex \else: \token_to_str:N #2 \fi: }

```

(End definition for __filehook_subst_add:nn and others.)

\use_ii_iii:nnn A variant of \use... to discard the first of three arguments.

Todo: this should move to expl3

```

240 \cs_gset:Npn \use_ii_iii:nnn #1 #2 #3 {#2 #3}

```

(End definition for \use_ii_iii:nnn.)

```

241 \ExplSyntaxOff
242 </2ekernel | latexrelease>
243 <latexrelease>\EndIncludeInRelease
244 <*2ekernel>

```

~~\declare@file@substitution~~ For two internals we provide L^AT_EX 2_ε names so that we can use them elsewhere in the kernel (and so that they can be used in packages if really needed, e.g., scrfile).

~~\undeclare@file@substitution~~

```

245 </2ekernel>
246 <*2ekernel | latexrelease>
247 <latexrelease>\IncludeInRelease{2020/10/01}%
248 <latexrelease>      {\declare@file@substitution}{File substitution}%
249 \ExplSyntaxOn
250 \cs_new_eq:NN \declare@file@substitution \__filehook_subst_add:nn
251 \cs_new_eq:NN \undeclare@file@substitution \__filehook_subst_remove:n
252 \ExplSyntaxOff
253 </2ekernel | latexrelease>
254 <latexrelease>\EndIncludeInRelease

```

We are not fully rolling back the file substitutions in case a rollback encounters a package that contains them, but is itself not setup for rollback. So we just bypass them and hope for the best.

```

255 <latexrelease>\IncludeInRelease{0000/00/00}%
256 <latexrelease>      {\declare@file@substitution}{File substitution}%
257 <latexrelease>
258 <latexrelease>\let \declare@file@substitution \@gobbletwo

```

```

259 <latexrelease>\let \undeclare@file@substitution \@gobble
260 <latexrelease>
261 <latexrelease>\EndIncludeInRelease
262 <*2ekernel)

```

(End definition for `\declare@file@substitution` and `\undeclare@file@substitution`. These functions are documented on page 5.)

```

263 <@=@>
264 \ExplSyntaxOff

```

2.6 Selecting a file (`\set@curr@file`)

`\set@curr@file` Now we hook into `\set@curr@file` to resolve a possible file substitution, and add `\@curr@file` `\@expl@@@filehook@set@curr@file@@nNN` at the end, after `\@curr@file` is set. `\@curr@file@reqd`

A file name is built using `\expandafter\string\csname<filename>\endcsname` to avoid expanding utf8 active characters. The `\csname` expands the normalization machinery and the routine to resolve a file substitution, returning a control sequence with the same name as the file.

It happens that when `<filename>` is empty, the generated control sequence is `\csname\endcsname`, and doing `\string` on that results in the file `csnameendcsname.tex`. To guard against that we `\ifx`-compare the generated control sequence with the empty `csname`. To do so, `\csname\endcsname` has to be defined, otherwise it would be equal to `\relax` and we would have false positives. Here we define `\csname\endcsname` to expand to itself to avoid it matching the definition of some other control sequence.

```

265 </2ekernel)
266 <*2ekernel | latexrelease)
267 <latexrelease> \IncludeInRelease{2021/06/01}%
268 <latexrelease>     {\set@curr@file}{Setting current file name}%
269 \def\set@curr@file#1{%
270   \begingroup
271     \escapechar\m@ne
272     \let\protect\string
273     \edef~{\string~}%
274     \expandafter\def\csname\expandafter\endcsname
275       \expandafter{\csname\endcsname}%

```

Two file names are set here: `\@curr@file@reqd` which is the file requested by the user, and `\@curr@file` which should be the same, except when we have a file substitution, in which case it holds the actual loaded file. `\@curr@file` is resolved first, to check if a substitution happens. If it doesn't, `\@expl@@@filehook@if@file@replaced@@TF` short-cuts and just copies `\@curr@file`, otherwise the full normalization procedure is executed.

At this stage the file name is parsed and normalized, but if the input doesn't have an extension, the default `.tex` is *not* added to `\@curr@file` because for applications other than `\input` (graphics, for example) the default extension may not be `.tex`. First check if the input has an extension, then if the input had no extension, call `\@expl@@@filehook@drop@extension@@N`. In case of a file substitution, `\@curr@file` will have an extension.

```

276   \@expl@@@filehook@if@no@extension@@nTF{#1}%
277     {\@tempwattrue}{\@tempwafalse}%
278   \@kernel@make@file@csname\@curr@file
279   \@expl@@@filehook@resolve@file@subst@@w {#1}%

```

```

280 \expl@@@filehook@if@file@replaced@@TF
281 {\kernel@make@file@csname\@curr@file@reqd
282 \expl@@@filehook@normalize@file@name@@w{#1}%
283 \if@tempswa \expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
284 {\if@tempswa \expl@@@filehook@drop@extension@@N\@curr@file \fi
285 \global\let\@curr@file@reqd\@curr@file}%
286 \expl@@@filehook@clear@replacement@flag@@
287 \endgroup}
288 /2kernel | latexrelease)
289 (latexrelease)\EndIncludeInRelease

290 (latexrelease)\IncludeInRelease{2020/10/01}%
291 (latexrelease) {\set@curr@file}{Setting current file name}%
292 (latexrelease)\def\set@curr@file#1{%
293 (latexrelease) \begingroup
294 (latexrelease) \escapechar\m@ne
295 (latexrelease) \expandafter\def\csname\expandafter\endcsname
296 (latexrelease) \expandafter{\csname\endcsname}%
297 (latexrelease) \@expl@@@filehook@if@no@extension@@nTF{#1}%
298 (latexrelease) {\@tempwattrue}{\@tempwafalse}%
299 (latexrelease) \kernel@make@file@csname\@curr@file
300 (latexrelease) \expl@@@filehook@resolve@file@subst@@w {#1}%
301 (latexrelease) \expl@@@filehook@if@file@replaced@@TF
302 (latexrelease) {\kernel@make@file@csname\@curr@file@reqd
303 (latexrelease) \expl@@@filehook@normalize@file@name@@w{#1}%
304 (latexrelease) \if@tempswa \expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
305 (latexrelease) {\if@tempswa \expl@@@filehook@drop@extension@@N\@curr@file \fi
306 (latexrelease) \global\let\@curr@file@reqd\@curr@file}%
307 (latexrelease) \expl@@@filehook@clear@replacement@flag@@
308 (latexrelease) \endgroup}
309 (latexrelease)\EndIncludeInRelease

310 (latexrelease)\IncludeInRelease{2019/10/01}%
311 (latexrelease) {\set@curr@file}{Setting current file name}%
312 (latexrelease)\def\set@curr@file#1{%
313 (latexrelease) \begingroup
314 (latexrelease) \escapechar\m@ne
315 (latexrelease) \xdef\@curr@file{%
316 (latexrelease) \expandafter\expandafter\expandafter\unquote@name
317 (latexrelease) \expandafter\expandafter\expandafter{%
318 (latexrelease) \expandafter|string
319 (latexrelease) \csname\@firstofone#1\@empty\endcsname}}%
320 (latexrelease) \endgroup
321 (latexrelease)}
322 (latexrelease)\EndIncludeInRelease

323 (latexrelease)\IncludeInRelease{0000/00/00}%
324 (latexrelease) {\set@curr@file}{Setting current file name}%
325 (latexrelease)\let\set@curr@file\undefined
326 (latexrelease)\EndIncludeInRelease
327 (*2kernel)

```

(End definition for \set@curr@file, \@curr@file, and \@curr@file@reqd. These functions are documented on page ??.)

```

\filehook@set@CurrentFile
\kernel@make@file@csname
\set@curr@file@aux

```

Todo: This should get internalized using @expl@ names

```

328 </2kernel>
329 <*2kernel | latexrelease>
330 <latexrelease>\IncludeInRelease{2020/10/01}%
331 <latexrelease>          {\@kernel@make@file@csname}{Make file csname}%
332 \def\@kernel@make@file@csname#1#2#3{%
333   \xdef#1{\expandafter\@set@curr@file@aux
334     \csname\expandafter#2\@firstofone#3\@nil\endcsname}}

```

This auxiliary compares `\<filename>` with `\csname\endcsname` to check if the empty `.tex` file was requested.

```

335 \def\@set@curr@file@aux#1{%
336   \expandafter\ifx\csname\endcsname#1%
337     .tex\else\string#1\fi}

```

Then we call `\@expl@@filehook@set@curr@file@@nNN` once for `\@curr@file` to set `\CurrentFile(Path)Used` and once for `\@curr@file@reqd` to set `\CurrentFile(Path)`. Here too the slower route is only used if a substitution happened, but here `\@expl@@filehook@if@file@replaced@@TF` can't be used because the flag is reset at the `\endgroup` above, so we check if `\@curr@file` and `\@curr@file@reqd` differ. This macro is issued separate from `\set@curr@file` because it changes `\CurrentFile`, and side-effects would quickly get out of control.

```

338 \def\@filehook@set@CurrentFile{%
339   \@expl@@filehook@set@curr@file@@nNN{\@curr@file}%
340   \CurrentFileUsed\CurrentFilePathUsed
341   \ifx\@curr@file@reqd\@curr@file
342     \let\CurrentFile\CurrentFileUsed
343     \let\CurrentFilePath\CurrentFilePathUsed
344   \else
345     \@expl@@filehook@set@curr@file@@nNN{\@curr@file@reqd}%
346     \CurrentFile\CurrentFilePath
347   \fi}
348 </2kernel | latexrelease>
349 <latexrelease>\EndIncludeInRelease
350 <*2kernel>

```

(End definition for \@filehook@set@CurrentFile, \@kernel@make@file@csname, and \@set@curr@file@aux. These functions are documented on page ??.)

`\@@_set_curr_file:nNN` When inputting a file, `\set@curr@file` does a file lookup (in `\input@path` and `\l_file_search_path_seq`) and returns the actual file name (`<base>` plus `<ext>`) in `\CurrentFileUsed`, and in case there's a file substitution, the requested file in `\CurrentFile` (otherwise both are the same). Only the base and extension are returned, regardless of the input (both `path/to/file.tex` and `file.tex` end up as `file.tex` in `\CurrentFile`). The path is returned in `\CurrentFilePath`, in case it's needed.

```

351 </2kernel>
352 <*2kernel | latexrelease>
353 <latexrelease>\IncludeInRelease{2020/10/01}%
354 <latexrelease>          {\@@_set_curr_file:nNN}{Set curr file}%
355 \ExplSyntaxOn
356 <@@=filehook>
357 \cs_new_protected:Npn \__filehook_set_curr_file:nNN #1
358   {
359     \exp_args:Nf \__filehook_file_parse_full_name:nN {#1}

```



```

360     \_filehook_set_curr_file_assign:nnnNN
361   }
362 \cs_new_protected:Npn \_filehook_set_curr_file_assign:nnnNN #1 #2 #3 #4 #5
363   {
364     \str_set:Nn #5 {#1}
365     \str_set:Nn #4 {#2#3}
366   }
367 \ExplSyntaxOff
368 </2ekernel | latexrelease>
369 <latexrelease>\EndIncludeInRelease
370 <*2ekernel>

```

(End definition for \@@_set_curr_file:nnn and \@@_set_curr_file_assign:nnnNN. These functions are documented on page ??.)

2.7 Replacing a file and detecting loops

```

\_filehook_resolve_file_subst:w Start by sanitizing the file with \_filehook_file_parse_full_name:nN then do
\_filehook_normalize_file_name:w \_filehook_file_subst_begin:nnn{<path>}{<name>}{<ext>}.
\_filehook_file_name_compose:nnn
371 </2ekernel>
372 <*2ekernel | latexrelease>
373 <latexrelease>\IncludeInRelease{2020/10/01}%
374 <latexrelease>    {\_filehook_resolve_file_subst:w}{Replace files detect loops}%
375 \ExplSyntaxOn
376 \cs_new:Npn \_filehook_resolve_file_subst:w #1 \@nil
377   { \_filehook_file_parse_full_name:nN {#1} \_filehook_file_subst_begin:nnn }
378 \cs_new:Npn \_filehook_normalize_file_name:w #1 \@nil
379   { \_filehook_file_parse_full_name:nN {#1} \_filehook_file_name_compose:nnn }
380 \cs_new:Npn \_filehook_file_name_compose:nnn #1 #2 #3
381   { \tl_if_empty:nF {#1} { #1 / } #2#3 }

```

Since the file replacement is done expandably in a \csname, use a flag to remember if a substitution happened. We use this in \set@curr@file to short-circuit some of it in case no substitution happened (by far the most common case, so it's worth optimizing). The flag raised during the file substitution algorithm must be explicitly cleared after the _filehook_if_file_replaced:TF conditional is no longer needed, otherwise further uses of _filehook_if_file_replaced:TF will wrongly return true.

```

flag\_filehook_file_replaced
\_filehook_if_file_replaced:TF
\_filehook_clear_replacement_flag:
382 \flag_new:n { \_filehook_file_replaced }
383 \cs_new:Npn \_filehook_if_file_replaced:TF #1 #2
384   { \flag_if_raised:nTF { \_filehook_file_replaced } {#1} {#2} }
385 \cs_new_protected:Npn \_filehook_clear_replacement_flag:
386   { \flag_clear:n { \_filehook_file_replaced } }

```

First off, start by checking if the current file ($\langle name \rangle + \langle ext \rangle$) has a declared substitution. If not, then just put that as the name (including a possible $\langle path \rangle$ in this case): this is the default case with no substitutions, so it's the first to be checked. The auxiliary _filehook_file_subst_tortoise_hare:nn sees that there's no replacement for #2#3 and does nothing else.

```

\_filehook_file_subst_begin:nnn
387 \cs_new:Npn \_filehook_file_subst_begin:nnn #1 #2 #3
388   {
389     \_filehook_file_subst_tortoise_hare:nn { #2#3 } { #2#3 }
390     { \_filehook_file_name_compose:nnn {#1} {#2} {#3} }
391   }

```

```

392 \ExplSyntaxOff
393 </2ekernel | latexrelease>
394 <latexrelease>\EndIncludeInRelease
395 <*2ekernel>

```

2.7.1 The Tortoise and Hare algorithm

```

\_filehook_file_subst_tortoise_hare:nn
\_filehook_file_subst_loop:NN
\_filehook_file_subst_loop:cc

```

If there is a substitution ($\langle true \rangle$ in the first `\cs_if_exist:cTF` below), then first check if there is no substitution down the line: this should be the second most common case, of one file replaced by another. In that case just leave the substitution there and the job is done. If any substitution happens, then the `\flag__filehook_file_replaced` is raised (conditionally, because checking if a flag is raised is much faster than raising it over and over again).

If, however there are more substitutions, then we need to check for a possible loop in the substitutions, which would otherwise put \TeX in an infinite loop if just an exhaustive expansion was used.

To detect a loop, the *Tortoise and Hare* algorithm is used. The name of the algorithm is an analogy to Aesop's fable, in which the Hare outruns a Tortoise. The two pointers here are the csnames which contains each file replacement, both of which start at the position zero, which is the file requested. In the inner part of the macro below, `_filehook_file_subst_loop:cc` is called with `\@file-subst@<file>` and `\@file-subst@\@file-subst@<file>`; that is, the substitution of $\langle file \rangle$ and the substitution of that substitution: the Tortoise walks one step while the Hare walks two.

Within `_filehook_file_subst_loop:NN` the two substitutions are compared, and if they lead to the same file it means that there is a loop in the substitutions. If there's no loop, `_filehook_file_subst_tortoise_hare:nn` is called again with the Tortoise at position 1 and the hare at 2. Again, the substitutions are checked ahead of the Hare pointer to check that it won't run too far; in case there is no loop in the declarations, eventually one of the `\cs_if_exist:cTF` below will go $\langle false \rangle$ and the algorithm will end; otherwise it will run until the Hare reaches the same spot as the tortoise and a loop is detected.

```

396 </2ekernel>
397 <*2ekernel | latexrelease>
398 <latexrelease>\IncludeInRelease{2020/10/01}%
399 <latexrelease> {\_filehook_file_subst_tortoise_hare:nn}{Tortoise and Hare}%
400 \ExplSyntaxOn
401 \cs_new:Npn \_filehook_file_subst_tortoise_hare:nn #1 #2 #3
402 {
403   \cs_if_exist:cTF { @file-subst@ #2 }
404   {
405     \flag_if_raised:nF { __filehook_file_replaced }
406     { \flag_raise:n { __filehook_file_replaced } }
407     \cs_if_exist:cTF { @file-subst@ \use:c { @file-subst@ #2 } }
408     {
409       \_filehook_file_subst_loop:cc
410       { @file-subst@ #1 }
411       { @file-subst@ \use:c { @file-subst@ #2 } }
412     }
413     { \use:c { @file-subst@ #2 } }
414   }
415   { #3 }
416 }

```

This is just an auxiliary to check if a loop was found, and continue the algorithm otherwise. If a loop is found, the `.tex` file is used as fallback and `__filehook_file_subst_cycle_error:cN` is called to report the error.

```

417 \cs_new:Npn \__filehook_file_subst_loop:NN #1 #2
418 {
419   \token_if_eq_meaning:NNTF #1 #2
420   {
421     .tex
422     \__filehook_file_subst_cycle_error:cN { @file-subst@ #1 } #1
423   }
424   { \__filehook_file_subst_tortoise_hare:nn {#1} {#2} {#2} }
425 }
426 \cs_generate_variant:Nn \__filehook_file_subst_loop:NN { cc }

```

Showing this type of error expandably is tricky, as we have a very limited amount of characters to show and a potentially large list. As a work around, several errors are printed, each showing one step of the loop, until all the error messages combined show the loop.

```

\__filehook_file_subst_cycle_error:NN
\__filehook_file_subst_cycle_error:cN

```

```

427 \cs_new:Npn \__filehook_file_subst_cycle_error:NN #1 #2
428 {
429   \__kernel_msg_expandable_error:nfff { kernel } { file-cycle }
430   {#1} { \use:c { @file-subst@ #1 } }
431   \token_if_eq_meaning:NNTF #1 #2
432   { \__filehook_file_subst_cycle_error:cN { @file-subst@ #1 } #2 }
433 }
434 \cs_generate_variant:Nn \__filehook_file_subst_cycle_error:NN { c }

```

And the error message:

```

435 \__kernel_msg_new:nnn { kernel } { file-cycle }
436 { File-loop!~#1~replaced-by~#2... }

```

(End definition for `__filehook_resolve_file_subst:w` and others.)

```

437 \ExplSyntaxOff
438 </2ekernel | latexrelease>
439 <latexrelease>\EndIncludeInRelease
440 <*2ekernel>
441 <@@=>

```

2.8 Preventing a package from loading

We support the use case of preventing a package from loading but not any other type of files (e.g., classes).

`\disable@package@load` defines `\@pkg-disable@<package>` to expand to some code `#2` instead of loading the package.

```

\disable@package@load
\reenable@package@load
\@disable@packageload@do
442 </2ekernel>
443 <*2ekernel | latexrelease>
444 <latexrelease>\IncludeInRelease{2020/10/01}%
445 <latexrelease>          {\disable@package@load}{Disable packages}%
446 \def\disable@package@load#1#2{%
447   \global\@namedef{@pkg-disable@#1.\@pkgextension}{#2}}

```

```

448 \def\@disable@package@load@do#1#2{%
449   \ifundefined{@pkg-disable@#1}{#2}%
450     {\@nameuse{@pkg-disable@#1}}
451
452   \reenable@package@load undefines \@pkg-disable@<package> to reallow loading
453   a package.
454
455 \def\reenable@package@load#1{%
456   \global\expandafter\let
457   \csname @pkg-disable@#1.\@pkgextension \endcsname \undefined}
458
459 </2ekernel | latexrelease>
460 <latexrelease>\EndIncludeInRelease
461 <latexrelease>\IncludeInRelease{0000/00/00}%
462 <latexrelease>     {\@disable@package@load}{Disable packages}%
463 <latexrelease>
464 <latexrelease>\let\@disable@package@load \@undefined
465 <latexrelease>\let\@disable@package@load@do\@undefined
466 <latexrelease>\let\reenable@package@load \@undefined
467 <latexrelease>\EndIncludeInRelease
468 <*2ekernel>

```

(End definition for `\@disable@package@load`, `\reenable@package@load`, and `\@disable@package@load@do`. These functions are documented on page 5.)

2.9 High-level interfaces for L^AT_EX

None so far and the general feeling for now is that the hooks are enough. Packages like `filehook`, etc., may use them to set up their interfaces (samples are given below) but for the now the kernel will not provide any.

2.10 Internal commands needed elsewhere

Here we set up a few horrible (but consistent) L^AT_EX_{2 ϵ} names to allow for internal commands to be used outside this module (and in parts that still use L^AT_EX_{2 ϵ} syntax. We have to unset the `@@` since we want double “at” sign in place of double underscores.

```

464 <@@=>
465 </2ekernel>
466 <*2ekernel | latexrelease>
467 <latexrelease>\IncludeInRelease{2020/10/01}%
468 <latexrelease>   {\@expl@@@filehook@if@no@extension@@nTF}{2e tmp interfaces}%
469 \ExplSyntaxOn
470 \cs_new_eq:NN \@expl@@@filehook@if@no@extension@@nTF
471   \__filehook_if_no_extension:nTF
472 \cs_new_eq:NN \@expl@@@filehook@set@curr@file@@nNN
473   \__filehook_set_curr_file:nNN
474 \cs_new_eq:NN \@expl@@@filehook@resolve@file@subst@@w
475   \__filehook_resolve_file_subst:w
476 \cs_new_eq:NN \@expl@@@filehook@normalize@file@name@@w
477   \__filehook_normalize_file_name:w
478 \cs_new_eq:NN \@expl@@@filehook@if@file@replaced@@TF
479   \__filehook_if_file_replaced:TF

```

```

480 \cs_new_eq:NN \@expl@@@filehook@clear@replacement@flag@@
481         \__filehook_clear_replacement_flag:
482 \cs_new_eq:NN \@expl@@@filehook@drop@extension@@N
483         \__filehook_drop_extension:N
484 \cs_new_eq:NN \@expl@@@filehook@file@push@@
485         \__filehook_file_push:
486 \cs_new_eq:NN \@expl@@@filehook@file@pop@@
487         \__filehook_file_pop:
488 \cs_new_eq:NN \@expl@@@filehook@file@pop@assign@@nnnn
489         \__filehook_file_pop_assign:nnnn
490 \ExplSyntaxOff

```

This one specifically has to be undefined because it is left over in the input stream from `\InputIfFileExists` and executed when `latexrelease` is loaded. It cannot be `\let` to `\undefined` otherwise it would error as well, so it is `\let` to `\relax` to be silently ignored when loading `\latexrelease`.

```

491 </2kernel | latexrelease>
492 <latexrelease>\EndIncludeInRelease
493 <latexrelease>
494 <latexrelease>\IncludeInRelease{0000/00/00}%
495 <latexrelease>    {\@expl@@@filehook@if@no@extension@@nTF}{2e tmp interfaces}%
496 <latexrelease>\let\@expl@@@filehook@file@pop@@\relax
497 <latexrelease>\EndIncludeInRelease
498 <*2kernel>

```

This ends the kernel code in this file.

```

499 </2kernel>

```

3 A sample package for structuring the log output

```

500 <*structuredlog>
501 <@@=filehook>
502 \ProvidesExplPackage
503     {structuredlog}{\ltfilehookdate}{\ltfilehookversion}
504     {Structuring the TeX transcript file}

```

`\g_filehook_nesting_level_int` Stores the current package nesting level.

```

505 \int_new:N \g_filehook_nesting_level_int

```

Initialise the counter with the number of files in the `\@currnamestack` (the number of items divided by 3) minus one, because this package is skipped when printing to the log.

```

506 \int_gset:Nn \g_filehook_nesting_level_int
507     { ( \tl_count:N \@currnamestack ) / 3 - 1 }

```

(End definition for `\g_filehook_nesting_level_int`.)

`_filehook_log_file_record:n` This macro is responsible for increasing and decreasing the file nesting level, as well as printing to the log. The argument is either `STOPTART` or `STOP` and the action it takes on the nesting integer depends on that.

```

508 \cs_new_protected:Npn \_filehook_log_file_record:n #1
509     {

```

```

510 \str_if_eq:nnT {#1} {START} { \int_gincr:N \g__filehook_nesting_level_int }
511 \iow_term:x
512 {
513   \prg_replicate:nn { \g__filehook_nesting_level_int } { = } ~
514   ( LEVEL ~ \int_use:N \g__filehook_nesting_level_int \c_space_tl #1 ) ~
515   \CurrentFileUsed

```

If there was a file replacement, show that as well:

```

516   \str_if_eq:NNF \CurrentFileUsed \CurrentFile
517   { ~ ( \CurrentFile \c_space_tl requested ) }
518   \iow_newline:
519 }
520 \str_if_eq:nnT {#1} {STOP} { \int_gdecr:N \g__filehook_nesting_level_int }
521 }

```

Now just hook the macro above in the generic file/before...

```

522 \AddToHook{file/before}{ \__filehook_log_file_record:n { START } }

```

...and file/after hooks. We don't want to install the file/after hook immediately, because that would mean it is the first time executed when the package finishes. We therefore put the declaration inside `\AddToHookNext` so that it gets only installed when we have left this package.

```

523 \AddToHookNext{file/after}
524 { \AddToHook{file/after}{ \__filehook_log_file_record:n { STOP } } }

```

(End definition for `__filehook_log_file_record:n`.)

```

525 <@@=
526 </structuredlog>

```

4 Package emulations

4.1 Package `atveryend` emulation

With the new hook management and the hooks in `\enddocument` all of `atveryend` is taken care of. We can make an emulation only here after the substitution functionality is available:

```

527 <*2kernel>
528 \declare@file@substitution{atveryend.sty}{atveryend-ltx.sty}
529 </2kernel>

```

Here is the package file we point to:

```

530 <*atveryend-ltx>
531 \ProvidesPackage{atveryend-ltx}
532 [2020/08/19 v1.0a
533   Emulation of the original atvery package^^Jwith kernel methods]

```

Here are new definitions for its interfaces now pointing to the hooks in `\enddocument`

```

534 \newcommand\AfterLastShipout {\AddToHook{enddocument/afterlastpage}}
535 \newcommand\AtVeryEndDocument {\AddToHook{enddocument/afteraux}}

```

Next one is a bit of a fake, but the result should normally be as expected. If not, one needs to add a rule to sort the code chunks in `enddocument/info`.

```

536 \newcommand\AtEndAfterFileList{\AddToHook{enddocument/info}}
537 \newcommand\AtVeryVeryEnd {\AddToHook{enddocument/end}}

```

`\BeforeClearDocument` This one is the only one we don't implement or rather don't have a dedicated hook in the code.

```

538 \ExplSyntaxOn
539 \newcommand\BeforeClearDocument[1]
540 { \AtEndDocument{#1}
541   \atveryend@DEPRECATED{BeforeClearDocument \tl_to_str:n{#1}}
542 }

543 \cs_new:Npn\atveryend@DEPRECATED #1
544 { \iow_term:x{=====~DEPRECATED~USAGE~#1~=====}}
545 \ExplSyntaxOff

```

(End definition for \BeforeClearDocument. This function is documented on page ??.)

```
546 \</atveryend-ltx>
```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
@@ commands:	
@@_set_curr_file:nNN	<u>351</u>
@@_set_curr_file_assign:nnnNN	<u>351</u>
\<filename>	<u>15</u>
A	
\AddToHook	<u>4</u> , <u>522</u> , <u>524</u> , <u>534</u> , <u>535</u> , <u>536</u> , <u>537</u>
\AddToHookNext	<u>21</u> , <u>523</u>
\AfterLastShipout	<u>534</u>
\AtEndAfterFileList	<u>536</u>
\AtEndDocument	<u>540</u>
\AtEndOfClass	<u>3</u>
\AtEndOfPackage	<u>3</u>
\AtVeryEndDocument	<u>535</u>
\AtVeryVeryEnd	<u>537</u>
B	
\BeforeClearDocument	<u>538</u>
\begingroup	<u>270</u> , <u>293</u> , <u>313</u>
C	
class/after	<u>3</u>
class/after/.	<u>3</u>
class/before	<u>3</u>
class/before/.	<u>3</u>
\clearpage	<u>3</u> , <u>4</u>
cs commands:	
\cs:w	<u>209</u> , <u>223</u> , <u>235</u> , <u>236</u>
\cs_end:	<u>209</u> , <u>223</u> , <u>235</u> , <u>236</u>
\cs_generate_variant:Nn	<u>426</u> , <u>434</u>
\cs_gset:Npn	<u>240</u>
\cs_gset:Npx	<u>211</u>
\cs_if_exist:NTF	<u>17</u> , <u>18</u> , <u>93</u> , <u>403</u> , <u>407</u>
\cs_new:Npn	<u>30</u> , <u>38</u> , <u>44</u> , <u>57</u> , <u>95</u> , <u>100</u> , <u>105</u> , <u>112</u> , <u>127</u> , <u>232</u> , <u>238</u> , <u>376</u> , <u>378</u> , <u>380</u> , <u>383</u> , <u>387</u> , <u>401</u> , <u>417</u> , <u>427</u> , <u>543</u>
\cs_new_eq:NN	<u>250</u> , <u>251</u> , <u>470</u> , <u>472</u> , <u>474</u> , <u>476</u> , <u>478</u> , <u>480</u> , <u>482</u> , <u>484</u> , <u>486</u> , <u>488</u>
\cs_new_protected:Npn	<u>49</u> , <u>62</u> , <u>70</u> , <u>79</u> , <u>206</u> , <u>220</u> , <u>357</u> , <u>362</u> , <u>385</u> , <u>508</u>
\cs_set:Npx	<u>209</u> , <u>223</u>
\cs_undefine:N	<u>225</u>
\csname	<u>13</u> , <u>17</u> , <u>195</u> , <u>274</u> , <u>275</u> , <u>295</u> , <u>296</u> , <u>319</u> , <u>334</u> , <u>336</u> , <u>453</u>
\csname\endcsname	<u>13</u> , <u>15</u>
\CurrentFile	<u>2</u> , <u>4</u> , <u>7</u> , <u>10</u> , <u>11</u> , <u>15</u> , <u>16</u> , <u>3</u> , <u>67</u> , <u>84</u> , <u>166</u> , <u>171</u> , <u>174</u> , <u>342</u> , <u>346</u> , <u>516</u> , <u>517</u>
\CurrentFilePath	<u>2</u> , <u>7</u> , <u>10</u> , <u>16</u> , <u>3</u> , <u>67</u> , <u>83</u> , <u>165</u> , <u>343</u> , <u>346</u>
\CurrentFilePathUsed	<u>2</u> , <u>3</u> , <u>66</u> , <u>81</u> , <u>163</u> , <u>340</u> , <u>343</u>
\CurrentFileUsed	<u>2</u> , <u>4</u> , <u>10</u> , <u>16</u> , <u>3</u> , <u>66</u> , <u>82</u> , <u>164</u> , <u>340</u> , <u>342</u> , <u>515</u> , <u>516</u>
D	
\DeclareRobustCommand	<u>148</u> , <u>182</u>
\def	<u>160</u> , <u>176</u> , <u>192</u> , <u>269</u> , <u>274</u> , <u>292</u> , <u>295</u> , <u>312</u> , <u>332</u> , <u>335</u> , <u>338</u> , <u>446</u> , <u>448</u> , <u>451</u>
\detokenize	<u>10</u>
E	
\edef	<u>161</u> , <u>168</u> , <u>273</u>
\else	<u>337</u> , <u>344</u>

else commands:	
\else:	239
\endcsname	13, 15, 195,
274, 275, 295, 296, 319, 334, 336, 453	
\enddocument	22
\endgroup	15, 287, 308, 320
\EndIncludeInRelease	
... 14, 23, 88, 140, 177, 189, 198,	
243, 254, 261, 289, 309, 322, 326,	
349, 369, 394, 439, 455, 462, 492, 497	
\escapechar	271, 294, 314
exp commands:	
\exp_after:wN	73, 234, 235
\exp_args:Ne	46, 97
\exp_args:Nee	129
\exp_args:Nf	32, 34, 359
\exp_args:NV	53
\exp_not:n	209, 223
\expandafter	13, 153, 154,
155, 167, 185, 195, 274, 275, 295,	
296, 316, 317, 318, 333, 334, 336, 452	
\ExplSyntaxOff	12, 86, 138,
241, 252, 264, 367, 392, 437, 490, 545	
\ExplSyntaxOn	7,
29, 92, 205, 249, 355, 375, 400, 469, 538	
F	
\fi	283, 284, 304, 305, 337, 347
fi commands:	
\fi:	239
file commands:	
\file_full_name:n	10, 35
\file_parse_full_name_apply:nN ..	
... 32, 47, 90, 93, 95	
\l_file_search_path_seq ...	2, 10, 16
file internal commands:	
_file_parse_full_name_area:nw .	
... 102, 105, 109	
_file_parse_full_name_auxi:nN .	
... 97, 100	
_file_parse_full_name_base:nw .	
... 108, 112, 124	
_file_parse_full_name_tidy:nnnN	
... 119, 120, 122, 127	
file/after	1
file/after/...	1
file/before	1
file/before/...	1
filehook internal commands:	
_filehook_clear_replacement_-	
flag:	382, 481
_filehook_drop_extension:N	44, 483
_filehook_drop_extension_-	
aux:nnn	54, 57
_filehook_file_name_compose:nnn	
... 216, 371, 390	
_filehook_file_parse_full_-	
name:nN	7,
16, 28, 30, 53, 236, 359, 377, 379	
_filehook_file_pop:	59, 487
_filehook_file_pop_assign:nnnn	
... 59, 489	
_filehook_file_push:	59, 485
_filehook_file_subst_begin:nnn	
... 16, 377, 387	
_filehook_file_subst_cycle_-	
error:NN	18, 422, 427
_filehook_file_subst_loop:NN ..	
... 17, 396	
_filehook_file_subst_tortoise_-	
hare:nn	17, 18, 389, 396
_filehook_full_name:nn	30
_filehook_if_file_replaced:TF .	
... 17, 382, 479	
_filehook_if_no_extension:nTF .	
... 44, 471	
\g_filehook_input_file_seq ..	7, 59
\l_filehook_internal_tl	59
_filehook_log_file_record:n ..	508
\g_filehook_nesting_level_int ..	
... 505, 510, 513, 514, 520	
_filehook_normalize_file_-	
name:w	371, 477
_filehook_resolve_file_subst:w	
... 371, 475	
_filehook_set_curr_file:nNN ...	
... 357, 473	
_filehook_set_curr_file_-	
assign:nnnNN	360, 362
_filehook_subst_add:nn	
... 12, 204, 206, 250	
_filehook_subst_empty_name_-	
chk:NN	206
_filehook_subst_file_normalize:Nn	
... 206	
_filehook_subst_remove:n .	206, 251
flag internal commands:	
\flag_filehook_file_replaced ..	17
\flag_filehook_file_replaced ..	382
flag commands:	
\flag_clear:n	386
\flag_if_raised:nTF	384, 405
\flag_new:n	382
\flag_raise:n	406
G	
\global	285, 306, 447, 452

group commands:		M	
\group_begin:	208, 222	msg commands:	
\group_end:	218, 230	\msg_error:nnn	75
	I		N
if commands:		\newcommand	534, 535, 536, 537, 539
\if_meaning:w	239		
\IfFileExists	149, 183, 193		O
\IfFormatAtLeastTF	11	\openin	1
\ifx	13, 336, 341		
\include	1, 3, 4, 7		P
include/after	4	package/after	3
include/after/...	4	package/after/...	3
include/before	4	package/before	3
include/before/...	4	package/before/...	3
include/end	4	prg commands:	
include/end/...	4	\prg_do_nothing:	132, 134
\IncludeInRelease		\prg_replicate:nn	513
.	5, 15, 27, 89, 144, 179, 190,	\protect	272
.	203, 247, 255, 267, 290, 310, 323,	\ProvidesExplPackage	502
.	330, 353, 373, 398, 444, 456, 467, 494	\ProvidesPackage	531
\includeonly	3, 4		
\input	1, 2, 6, 7, 14		R
\InputIfFileExists	7, 9, 10, 20, 143	\relax	13, 20, 496
int commands:		\RequirePackage	2
\int_gdecr:N	520		
\int_gincr:N	510		S
\int_gset:Nn	506	scan internal commands:	
\int_new:N	505	\s__file_stop	
\int_set:Nn	210, 224	103, 105, 108, 110, 112, 125
\int_use:N	514	seq commands:	
iow commands:		\seq_gpop:NNTF	72
\iow_newline:	518	\seq_gpush:Nn	64
\iow_term:n	511, 544	\seq_if_exist:NTF	60
		\seq_new:N	61
		str commands:	
	J	\str_if_eq:NNTF	516
\jobname	10	\str_if_eq:nnTF	131, 510, 520
		\str_set:Nn	364, 365
	K	\string	10, 13, 272, 273, 318, 337
kernel internal commands:			
_kernel_file_name_sanitize:n	98		T
_kernel_msg_expandable_-		TeX and L ^A T _E X 2 _ε commands:	
error:nnnn	429	\@input	172, 186, 194
_kernel_msg_new:nnn	435	\@addtofilelist	169, 186, 194
		\@clsextension	10
	L	\@curr@file	13–15, 265, 339, 341
\latexrelease	20	\@curr@file@reqd	14, 15, 265, 341, 345
\let	20, 18, 19, 20, 21, 147, 187, 188, 195,	\@currnamestack	21, 507
.	196, 197, 258, 259, 272, 285, 306,	\@disable@packageload@do	442
.	325, 342, 343, 452, 459, 460, 461, 496	\@empty	319
\LoadPackageWithOptions	2	\@expl@@@filehook@clear@replacement@flag@@	
\long	192	286, 307, 480
\lthookdate	503	\@expl@@@filehook@drop@extension@@N	
\lthookversion	503	14, 283, 284, 304, 305, 482

<code>\@expl@@@filehook@file@pop@@</code> . . .	<code>\declare@file@substitution</code> 4 , 245 , 528
. 157 , 486 , 496	<code>\disable@package@load</code> 5 , 19 , 442
<code>\@expl@@@filehook@file@pop@assign@@nnnn</code>	<code>\filename@ext</code> 10
. 11 , 162 , 488	<code>\if@tempswa</code> 283 , 284 , 304 , 305
<code>\@expl@@@filehook@file@push@@</code> . . .	<code>\input@path</code> 2 , 10 , 16
. 151 , 484	<code>\m@ne</code> 271 , 294 , 314
<code>\@expl@@@filehook@if@file@replaced@@TF</code>	<code>\reenable@package@load</code> 5 , 19 , 442
. 14 , 15 , 280 , 301 , 478	<code>\reserved@a</code> 161 , 167 , 168 , 169
<code>\@expl@@@filehook@if@no@extension@@nTF</code>	<code>\set@curr@file</code> 13 , 15–17 , 265
. 276 , 297 , 468 , 470 , 495	<code>\string@makeletter</code> 169
<code>\@expl@@@filehook@normalize@file@name@@w</code>	<code>\undeclare@file@substitution</code> 4 , 245
. 282 , 303 , 476	<code>\unqu@tefilef@und</code> 143
<code>\@expl@@@filehook@resolve@file@subst@@w</code>	<code>\unquote@name</code> 316
. 279 , 300 , 474	tex commands:
<code>\@expl@@@filehook@set@curr@file@@nNN</code>	<code>\tex_escapechar:D</code> 210 , 224
. 13 , 15 , 339 , 345 , 472	tl commands:
<code>\@file-subst@{file}</code> 12	<code>\c_space_tl</code> 514 , 517
<code>\@filef@und</code> 10 , 155 , 172 , 186 , 194	<code>\tl_count:N</code> 507
<code>\@filehook@set@CurrentFile</code> . 152 , 328	<code>\tl_gset:Nn</code> 51
<code>\@firstofone</code> 319 , 334	<code>\tl_if_empty:nTF</code>
<code>\@gobble</code> 259 40 , 46 , 58 , 107 , 114 , 116 , 118 , 381
<code>\@gobbletwo</code> 258	<code>\tl_new:N</code> 8 , 9 , 10 , 11 , 59
<code>\@ifundefined</code> 449	<code>\tl_set:Nn</code> 81 , 82 , 83 , 84
<code>\@input</code> 1	<code>\tl_to_str:n</code> 541
<code>\@input@file@exists@with@hooks</code> . 143	<code>\tl_trim_spaces:n</code> 41 , 42
<code>\@kernel@make@file@csname</code>	token commands:
. 278 , 281 , 299 , 302 , 328	<code>\token_if_eq_meaning:NNTF</code> . . 419 , 431
<code>\@namedef</code> 447	<code>\token_to_str:N</code> 239
<code>\@nameuse</code> 450	
<code>\@nil</code> 168 , 176 , 334 , 376 , 378	U
<code>\@onefilewithoptions</code> 7	use commands:
<code>\@pkgextension</code> 447 , 453	<code>\use:N</code> 407 , 411 , 413 , 430
<code>\@set@curr@file@aux</code> 328	<code>\use_ii_iii:nnn</code> 214 , 228 , 240
<code>\@swaptwoargs</code> 153 , 167 , 185	<code>\use_iii:nnn</code> 47
<code>\@tempswafalse</code> 277 , 298	<code>\use_none:n</code> 131 , 134
<code>\@tempswatru</code> 277 , 298	<code>\UseHook</code> 2 , 3 , 9 , 170 , 171 , 174 , 175
<code>\@undefined</code>	<code>\usepackage</code> 1–3
. 20 , 18 , 19 , 20 , 21 , 147 , 187 , 188 ,	
195 , 196 , 197 , 325 , 453 , 459 , 460 , 461	X
<code>\atveryend@DEPRECATED</code> 541 , 543	<code>\xdef</code> 315 , 333